

BWM 300 + BF capillary matting

Standard capillary matting, made from 100% recycled synthetic fibers. Equipped with a black anti algae foil, with a thickness of 30 µm. Contains no natural fibers such as Jute or Cotton.

BWM 300 + BF capillary matting offers a high water capacity in combination with a low capillary function. BF stands for black anti algae foil, the foil is wrapped loosely on the capillary matting and has a fine perforation.

Functions of the black anti algae foil:

- ❖ Preventing root growth in the capillary matting
- ❖ Prevents the growth of algae
- ❖ Prevention of unnecessary evaporation of water
- ❖ Extending the life of the capillary matting
- ❖ Provide protection against mechanical influences, such as sweeping or walking

BWM 300 + BF:

Weight: 300 gr/m²
 Anti-algae foil: Black - 30 µm
 Water capacity: 4,0 to 5,0 liter/m²

Lengths: 40 and 50 meter
 Widths: 8 to 250 cm

Customization:

Henofa has punching and cutting machines to provide customization, for selling tables, cultivation gutters, container fields and deviating lengths. For more information, please send us a email on info@henofa.com.

Technical specification	Non-woven capillary matting	
<u>Composition:</u>	<u>Nominal:</u>	<u>Tolerance:</u>
Fiber composition	Recycling fibers	
Weight (gr/m ²)	350	5%
Anti-algae foil	Black, 30 µm	
Thickness (mm)	3,5	5%
Tensile-strength (kg/cm ²) Length-dry	5,0	
Tensile-strength (kg/cm ²) Width-dry	5,0	
Tensile-strength (kg/cm ²) Length-wet	5,0	
Tensile-strength (kg/cm ²) Width-wet	5,0	
Absorption capacity (ltr/m ²)	4,0 to 5,0	
Standard Length	40 or 50 meter	
Colour	Multi-colour	